

**sikkens**

**NEW: ENVIRONMENTALLY  
AND USER FRIENDLY  
SANDING SEALER!**



# CETOL WP 575

For a better wood  
surface look!



**AkzoNobel**



The Cetol WP 575 sanding sealer primarily serves the wood preparation to visually improve the subsequent coating quality. All water-soluble and/or solvent borne Sikkens Joinery paint and varnish systems can be used on the precision ground wood surface pre-treated in this way.



Cetol WP 575 is a water-soluble colorless sanding sealer for parts made from softwood and hardwood. Use Cetol WP 575 for the pre-treatment of the wood in order to produce an even and visually more appealing wood surface. After drying, a wood finish is enough to optimally prepare the surface for further coating with paint

or varnish systems. It is intended for use indoors and outdoors. In a standard climate, the sanding sealer is dust-dry after 30 minutes, sandable after around four hours and ready for treatment after approx. four to six hours.



### AT A GLANCE:

**Application:**   
For dimensionally stable wooden parts

**Processing:**    
Dip and brush coating

**Binder type:** Special polymer dispersion

**Consumption:** 40-50 ml/m<sup>2</sup>, depending on applied wet layer thickness per coat

**Colour tone:** colorless

**Packsize:** 5 litres, concentrate

### PRODUCT ADVANTAGES:

- More homogeneous wood surface
- Even absorption of the subsequent water-proofing and/or primer
- Fewer sources of streaks, less wrinkling
- No sanding of the water-proofing necessary thanks to the professional wood pre-treatment and only minimal, slight intermediate sanding necessary after primer or mid coat
- Environmentally friendly and health-conscious for you as the user because the sanding dust is free of biocide

Our technical data sheets and safety data sheets can be found for download at: [www.sikkens-joinery.com](http://www.sikkens-joinery.com)

**Do you have questions about our products?  
We are here to help:**

Akzo Nobel  
Wood Finishes and Adhesives  
Akzo Nobel Wood Coatings GmbH  
Vitalisstrasse 198–226  
50827 Cologne · Germany  
Tel. +49 221 58 81-0  
Fax +49 221 58 81-293  
[sikkens-holzbau-info@akzonobel.com](mailto:sikkens-holzbau-info@akzonobel.com)  
[www.sikkens-joinery.com](http://www.sikkens-joinery.com)

Sikkens is an AkzoNobel brand



**9i fchW bJWU**

**AH Ybg**  
ÒÈÀ^} ã^|[ ~ 232  
16341 ŠWÚUŠĚÁ@}•  
T^|.: 210 99 59 397  
Øæ.: 210 99 59 398  
[euroath@otenet.gr](mailto:euroath@otenet.gr)

**H YggUcb]\_]**  
QãÈÀ^ ãĀ Áĵ ã[ •ÉÁ7ÉÚÈĚĀ J8  
57022 V@•• ãĀ ] ã Ā  
T^|.: 2310 796 950  
Øæ.: 2310 790 783  
[info@eurotechnica.gr](mailto:info@eurotechnica.gr)