

FEX-RS

Shutter screw

for snap fastening of roller shutter guides

FEX®-RS: Snap fastening of profiles

- Needle point: no pre-drilling of plastic profile required
- Sharp thread extending to just below the head
- Collated available on request




Shutter screw

with needle point for snap fastening of roller shutter guides

The **FEX®-RS** self-drilling screw is driven into the frame profile.

The combination of a sharp, 5-mm wide thread with optimised snap-on head geometry provides excellent grip, withstanding the high axial tensile forces that occur in snap-on profiles such as shutter guides, drip covers, covering sections and wall connection profiles.






FEX®-RS

Shutter screw with snap-on head





Cross recess H 2

Profile system		Dimensions					Pack size			
Desig- nation		Nom. Ø	Length	Collar Ø	Head height	Bit size	ABC box	Master carton	Collated	ABC box
		d _n [mm]	l _g [mm]	d _k [mm]	h _k [mm]		[quantity]	[quantity]	[quantity per belt]	[20 belts]
RS-1	VEKA, Brügmann	5,0	10	9,5	6,1	H2	400	4.000	25	500
RS-2	Rehau, KBE, Golde, Inautic, Helmitin	5,0	10	10,4	5,8	H2	400	4.000	25	500
RS-3	Trocal, Stöckel, Menke	5,0	10	12,0	5,8	H2	400	4.000	25	500
RS-4	Kömmerling	5,0	10	11,0	7,6	H2	400	4.000	25	500
RS-5	Gealan	5,0	10	11,0	7,6	H2	400	4.000	25	500
RS-6	Inautic	5,0	10	9,5	4,0	H2	400	4.000	25	500







Shutter screw with needle point for fixing shutter guides, drip covers, covering sections and wall connection profiles.

■ Thread:

Sharp and wide 40° thread extending to just below the head.

Point:

Needle point: no-predrilling of plastic profile required.

Corrosion protection:

Bright galvanised, plating thickness 8–10 µm.

SPAX UK Ltd.

ALTENLOH, BRINCK & CO - GROUP

UNIT 9 · CALIBRE INDUSTRIAL ESTATE · LACHES CLOSE FOUR ASHES · WOLVERHAMPTON · WEST MIDLANDS · WV10 7DZ · GREAT BRITAIN TEL +44 (0) 1902-70 33 55 · FAX -70 33 59 · uk@spax.com · www.spax.com