

Spezial Intensivreiniger IR

Product description

IR Special Intensive Cleaner is an effective cleaning agent for all floor types such as parquet, plastic, cork, PVC, linoleum, natural and artificial stone floors, tiles, rubber floors etc.; especially suitable for floor surfaces cleaned with Naturtrend products. Well suited for cleaning equipment and machinery, which are used to process Zweihorn water lacquers or Naturtrend products.

Range of application

For basic cleaning of waxed or oiled floors prior to re-structuring as well as for cleaning equipment and machinery after using Zweihorn water lacquers or Naturtrend products. Removes old layers of self-shining materials, polymer layers, wax, oil and other dirt.

Surfaces

1. Basic cleaning of oiled or waxed floors:

Use Special IR Intensive Cleaner undiluted and allow it to soak in. The cleaning effect is intensified by using a scrubbing brush, cleaning cloth or floor washing machine with hard bristles. Do not allow Special IR Intensive Cleaner to dry in, break area you are working on down into sections if you have a larger job. Pick up dissolved dirt immediately and re-wipe with clear water. Before cleaning sensitive surfaces such as linoleum, high gloss areas and stained surfaces, perform a test in an unapparent area. You may want to dilute Special IR Intensive Cleaner with a maximum ratio of 1:5. You will need 1 litre (undiluted) for 8-10² of floor.

Oiled, waxed and stained surfaces must be re-treated following this basic cleaning. Use one of our many Naturtrend products for this purpose, e.g. Hartöl NHO (NHO Hard Oil), Projektöl NPO (NPO Project Oil), Einschicht-Hartwachsöl NWO (Single Layer Hard Wax Oil NWO) or Hartwachs-fest NHW (NHW Hard Wax - solid). Use Naturtrend Wachslotion NWL (Naturtrend Wax Lotion) only on surfaces that were previously treated with NWL. See Technical Datasheets for processing instructions.

2. Cleaning of equipment and machines:

Special IR Intensive Cleaner is used straight (undiluted). Severely dirty equipment (e.g. spray guns) can also be soaked in an immersion bath containing IR. After treatment/cleaning, the equipment/machinery must be thoroughly rinsed or wiped clean with water.

Product data

Batch sizes	2,5l,
Shelf life in unopened original batches	2 years

Special notes

- Wear rubber gloves when using IR
- Keep out of reach of children
- Material is sensitive to frost. Do not store or transport at temperatures below +5°C
- Special IR Intensive Cleaner is colour-neutral on oak and cork

Zweihorn products are produced for the professional user, who has a basic knowledge of the stockturn and the application of stains, varnishes, glazes and glues. The user information for our qualities given in the leaflets should be regarded as non-binding recommendations. They are based on our test series and experiences and should facilitate and promote the work of our clients. A possible necessary adjustment to the individual working conditions lies within your responsibility. If in any doubt, our material experts as well as our application and laboratory technicians will try to help you as best as they can. We guarantee of course the impeccable quality of our products based on our General Sales and Delivery Conditions. All current technical data sheets are herewith voided. The use of the final product lies entirely within the responsibility of the buyer. As long as we haven't guaranteed in writing specific characteristics and suitabilities of the products for a contractually agreed purpose, any advice or information given regarding the application, even if the advice or information is given to the best of our knowledge, will be non-binding. Nor does it relieve the buyer, either from his own inspection, and if need be through a trial processing. Furthermore, we are only liable according to Chapter 1 of our General Conditions for advice either given or rejected, which does not refer to the characteristics and use of the delivered product..