

# SAFETY DATA SHEET

Keimfix SP Kontakt



## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### Identification of the substance or mixture

**Product name** : Keimfix SP Kontakt**Product code** : KFSP

### Use of the substance/mixture

**Product use** : Industrial surface coating for wood.

### Company/undertaking identification

**Manufacturer** : Akzo Nobel Deco GmbH, Geschäftsbereich Zweihorn  
 Düsseldorfstraße 96-100  
 D-40721 Hilden  
 Deutschland  
 Tel: (+49) 0221-5881-0  
 Fax: (+49) 0221-5881-355  
 internet: www.zweihorn.com

**e-mail address of person responsible for this SDS** : sdbinfo@akzonobeldeco.de

## 2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : F; R11  
 Repr. Cat. 3; R63  
 Xn; R48/20  
 Xi; R38  
 R67  
 N; R51/53

**Physical/chemical hazards** : Highly flammable.

**Human health hazards** : Possible risk of harm to the unborn child. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Irritating to skin. Vapours may cause drowsiness and dizziness.

**Environmental hazards** : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC or assigned an occupational exposure limit.

Chemical name	CAS number	%	Number	Classification
toluene	108-88-3	25 - 50	203-625-9	F; R11 [1] [2] Repr. Cat. 3; R63 Xn; R48/20, R65 Xi; R38 R67
heptane	142-82-5	10 - 25	205-563-8	F; R11 [1] [2] Xn; R65 Xi; R38 R67 N; R50/53
ethyl acetate	141-78-6	2.5 - 10	205-500-4	F; R11 [1] [2] Xi; R36 R66, R67
butanone	78-93-3	2.5 - 10	201-159-0	F; R11 [1] [2] Xi; R36

**Date of issue/Date of revision** : 2010-08-10.**Page:** 1/7

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

See section 16 for the full text of the R-phrases declared above				R66, R67
--	--	--	--	----------

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

**Occupational exposure limits, if available, are listed in section 8.**

### 4. FIRST AID MEASURES

#### First-aid measures

- |                     |   |
|---------------------|---|
| <b>General</b>      | : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice. |
| <b>Inhalation</b>   | : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.      |
| <b>Skin contact</b> | : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.  |
| <b>Eye contact</b>  | : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.   |
| <b>Ingestion</b>    | : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.  |

### 5. FIRE-FIGHTING MEASURES

- |   |   |
|---|---|
| <b>Extinguishing media</b>                | : Recommended: alcohol-resistant foam, CO <sub>2</sub> , powders.   |
| <b>Extinguishing media not to be used</b> | : Do not use water jet.   |
| <b>Special exposure hazards</b>           | : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. |

### 6. ACCIDENTAL RELEASE MEASURES

- |                                  |   |
|----------------------------------|---|
| <b>Personal precautions</b>      | : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). |
| <b>Environmental precautions</b> | : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.  |
| <b>Methods for cleaning up</b>   | : Preferably clean with a detergent. Avoid using solvents.  |

**Note: see section 8 for personal protective equipment and section 13 for waste disposal.**

### 7. HANDLING AND STORAGE

- |                 |   |
|-----------------|---|
| <b>Handling</b> | : Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. |
|-----------------|---|

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

To dissipate static electricity during transfer, earth drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

## 7. HANDLING AND STORAGE

Keep away from heat, sparks and flame. No sparking tools should be used.

Keep container tightly closed.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Put on appropriate personal protective equipment (see section 8).

Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

### Storage

- : Store in accordance with local regulations. Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. Keep away from: oxidising agents, strong alkalis, strong acids.
- No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not empty into drains.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Ingredient name</u>	<u>Occupational exposure limits</u>
toluene	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007). Absorbed through skin.</b> STEL: 384 mg/m <sup>3</sup> 15 minute(s). STEL: 100 ppm 15 minute(s). TWA: 191 mg/m <sup>3</sup> 8 hour(s). TWA: 50 ppm 8 hour(s).
heptane	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007).</b> TWA: 500 ppm 8 hour(s).
ethyl acetate	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007).</b> STEL: 400 ppm 15 minute(s). TWA: 200 ppm 8 hour(s).
butanone	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007). Absorbed through skin.</b> STEL: 899 mg/m <sup>3</sup> 15 minute(s). STEL: 300 ppm 15 minute(s). TWA: 600 mg/m <sup>3</sup> 8 hour(s). TWA: 200 ppm 8 hour(s).

### Exposure controls

- : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

### Occupational exposure controls

#### Respiratory system

- : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- |  |  |
|--|--|
| <b>Skin and body</b>                   | : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.  |
| <b>Hands</b>                           |  |
| <b>Gloves</b>                          | : For prolonged or repeated handling, use the following type of gloves:<br><br>Recommended: foil<br>Not recommended: nitrile rubber, neoprene, PVC<br>May be used: butyl rubber, fluor rubber<br><br>Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.<br><br>The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. |
| <b>Eyes</b>                            | : Use safety eyewear designed to protect against splash of liquids.  |
| <b>Environmental exposure controls</b> | : Do not allow to enter drains or watercourses.  |

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- |                         |   |
|-------------------------|---|
| <b>Physical state</b>   | : Liquid.   |
| <b>Flash point</b>      | : Closed cup : -4 °C  |
| <b>Density</b>          | : 0.85 g/cm <sup>3</sup>                                    |
| <b>Vapour density</b>   | : > 1 (Air = 1) (Calculated value for the mixture)          |
| <b>Explosion limits</b> | : Greatest known range: Lower: 1.8% Upper: 11.5% (butanone) |

## 10. STABILITY AND REACTIVITY

- |   |   |
|---|---|
| <b>Conditions to avoid</b>              | : Stable under recommended storage and handling conditions (see section 7). When exposed to high temperatures may produce hazardous decomposition products. |
| <b>Materials to avoid</b>               | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.                            |
| <b>Hazardous decomposition products</b> | : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.                                   |

## 11. TOXICOLOGICAL INFORMATION

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

## 12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself.  
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 3 and 15 for details.

### Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
-------------------------	------	--------	---------	----------

## 12. ECOLOGICAL INFORMATION

heptane	-	Acute LC50 375 mg/l Fresh water	Fish - Mozambique tilapia - Tilapia mossambica - 99 mm - 10 g	96 hours
---------	---	---------------------------------	---	----------

**Conclusion/Summary** : Not available.

**Persistence/degradability**

**Conclusion/Summary** : Not available.

**PBT** : Not applicable.

**vPvB** : Not applicable.

## 13. DISPOSAL CONSIDERATIONS

Do not allow to enter drains or watercourses.  
Dispose of according to all federal, state and local applicable regulations.

**Hazardous waste** : The classification of the product meets the criteria for hazardous waste. (EWC 08 01 11)

**Packaging** : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

## 14. TRANSPORT INFORMATION

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.


**Land - road/railway**

**UN number** : UN1263  
**Transport document name** : PAINT RELATED MATERIAL  
**Special provision 640** : D  
**ADR/RID Class** : 3  
**Packing group** : II  
**ADR/RID Label** :



**Sea**

**UN number** : UN1263  
**Proper shipping name** : PAINT RELATED MATERIAL  
**Marine pollutant substances** : heptane  
**IMDG Class** : 3  
**Packing group** : II  
**IMDG Label** :





**Marine pollutant** : Yes.

**Air**

**UN number** : UN1263  
**Proper shipping name** : PAINT RELATED MATERIAL  
**ICAO/IATA Classification** : 3  
**Packing group** : II

<b>14. TRANSPORT INFORMATION</b>
----------------------------------

ICAO/IATA label :  

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**EU regulations** : The product is classified and labelled for supply in accordance with the Directive 1999/45/EC as follows:

**Hazard symbol or symbols** : 

Highly flammable, Harmful, Dangerous for the environment

**Risk phrases** : R11- Highly flammable.  
 R63- Possible risk of harm to the unborn child.  
 R48/20- Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
 R38- Irritating to skin.  
 R67- Vapours may cause drowsiness and dizziness.  
 R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases** : S23- Do not breathe vapour or spray.  
 S36/37- Wear suitable protective clothing and gloves.  
 S51- Use only in well-ventilated areas.

**Contains** : toluene

The information in this Safety Data Sheet is required pursuant to Annex II to Regulation (EC) No 1907/2006.

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

<b>16. OTHER INFORMATION</b>
------------------------------

**Full text of R-phrases referred to in sections 2 and 3 - United Kingdom (UK)** : R11- Highly flammable.  
 R63- Possible risk of harm to the unborn child.  
 R48/20- Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
 R65- Harmful: may cause lung damage if swallowed.  
 R36- Irritating to eyes.  
 R38- Irritating to skin.  
 R66- Repeated exposure may cause skin dryness or cracking.  
 R67- Vapours may cause drowsiness and dizziness.  
 R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Date of issue/ Date of revision** : 2010-08-10.

**Notice to reader**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

