

Kaligenbeize ORF 19945

Product description

Liquid, ready to use, watery wood etchant on an alkali basis, which reacts chemically with the contents of the wood.

Range of application

Zweihorn Kaligenbeize can be used indoors on all types of wood.

Preparation

Graded, sharp groundwood pulp with 120-150 granulation. Careful removal of the wood dust from the pores.

Application

Shake or stir thoroughly before use! Apply Zweihorn Kaligenbeize ORF 19945 generously using a brush made of synthetic material. Wash lavishly with water and dry after being left to dry over night. Before further processing, the dried surface is smoothed with 280-320 granulation.

Application methods

Use a brush made of synthetic materials.

Drying time

(at room temperature 20°C, 65 % relative humidity) 24 hours at room temperature. The water must be removed completely from the surface. Heat and air movement shorten the drying process.

Coating

All Zweihorn wood varnishes can be applied on top of the Zweihorn Kaligenbeize. The Zweihorn Naturtrend product can also be applied to surfaces that are not.

Product data

Batch sizes	0,75 l, 5 l
Viscosity at delivery DIN-4mm	12 sec.
Shelf life in unopened original batches	2 years

Further information can be obtained from the label and the Safety Data Sheet 91/155/EWG, which you can download from the Internet.

Special notes

- Kaligenbeize are caustic! Protect your eyes! Wear protective glasses! Avoid contact with skin and clothes!
- Wear gloves during work!
- If you suffer a caustic burn nonetheless, rinse with water immediately and consult a doctor!
- Do not use metal containers or metal appliances!
- It does not contain heavy metals, as e.g., lead, chromium, mercury, cadmium.

Zweihorn products are produced for the professional user, who has a basic knowledge of the stockturn and the application of stains, varnishes, glazes and glues. The user information for our qualities given in the leaflets should be regarded as non-binding recommendations. They are based on our test series and experiences and should facilitate and promote the work of our clients. A possible necessary adjustment to the individual working conditions lies within your responsibility. If in any doubt, our material experts as well as our application and laboratory technicians will try to help you as best as they can. We guarantee of course the impeccable

quality of our products based on our General Sales and Delivery Conditions. All current technical data sheets are herewith voided. The use of the final product lies entirely within the responsibility of the buyer. As long as we haven't guaranteed in writing specific characteristics and suitabilities of the products for a contractually agreed purpose, any advice or information given regarding the application, even if the advice or information is given to the best of our knowledge, will be non-binding. Nor does it relieve the buyer, either from his own inspection, and if need be through a trial processing. Furthermore, we are only liable according to Chapter 1 of our General Conditions for advice either given or rejected, which does not refer to the characteristics and use of the delivered product.