

Egalisator S 9025

Product description

Egalisator S 9025 compensates for the different absorbency of wood, especially in the case of veneer with butt joints.

Range of application

Egalisator S 9025 is used as so-called pre-stain for compensating colouring. Veneer of all kind, applied with butt joints, having different absorbency characteristics with regard to stains are coated with S 9025 in order to avoid irregular stain appearance.

Surfaces

All types of wood with different absorbency characteristics.

Preparation

In case of raw wood surfaces, carry out wood sanding in several steps (120/150/perhaps 180 grit paper) and dust well.

Application

Mix 25 ml of Egalisator S 9025 with 1 litre of cold water. Richly apply with sponge, brush or spraying gun. After drying overnight, sand with fine sandpaper (400 grit paper); Caution: Do not grind through! Further treatment with Zweihorn solvent stains. For further treatment with water soluble stains, Egalisator S 9025, solved in water, can also be used if applied appropriately. Always make a test staining in such a case. Overpainting should only be made with light resistant, colourless varnishes such as Crystallit or DiaDur.

Drying time

Drying overnight

Product data

Batch size	1 kg
Shelf life in unopened original batches	approx. 1 year

Further information can be obtained from the label and the Safety Data Sheet 91/155/EWG, which you can download from the Internet under www.zweihorn.com or which you can request from us.

Special notes

- Do not sand too deep so that the effect of the Egalisator is not lost.
- The material is frost sensitive. Do not store nor transport below 5°C.

Zweihorn products are produced for the professional user, who has a basic knowledge of the use and the application of stains, varnishes, glazes and glues. The user information for our qualities given in the leaflets should be regarded as non-binding recommendations. They are based on our test series and experiences and should facilitate and promote the work of our clients. Any adjustment to the individual working conditions, which might be possible, lies within your responsibility. If in any doubt, our material experts as well as our application and laboratory technicians will try to help you as best as they can. We guarantee of course the impeccable quality of our products based on our General Sales and Delivery Conditions. The use of the final product lies entirely within the responsibility of the buyer. As long as we have not guaranteed in writing specific characteristics and suitability of the products for a contractually agreed purpose, any advice or information given regarding the application, even if the advice or information is given to the best of our knowledge, will be non-binding. Nor does it relieve the buyer, either from his own inspection, and if need be through a trial processing. Furthermore, we are only liable according to Chapter 1 of our General Conditions for advice either given or rejected, which does not refer to the characteristics and use of the delivered product.

Applicable is the current Technical Data Sheet, which can be downloaded under www.zweihorn.com. Previous technical data sheets are voided with the issue of a new version.

Date of issue: 3. August 2006