## SAFETY DATA SHEET



**Unocryl Parkettgrund** 

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation

Product name : Unocryl Parkettgrund

Product code : UC-PG

Use of the substance/preparation

**Product use** : Industrial surface coating for wood.

Company/undertaking identification

Manufacturer : Akzo Nobel Deco GmbH, Geschäftsbereich Zweihorn

Düsseldorferstraße 96-100

D-40721 Hilden Deutschland

Tel: (+49) 0221-5881-0 Fax: (+49) 0221-5881-355 internet: www.zweihorn.com

e-mail address of person responsible for this SDS

: sdbinfo@akzonobeldeco.de

### 2. HAZARDS IDENTIFICATION

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Not classified.

Additional warning phrases : Safety data sheet available for professional user on request.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC or assigned an occupational exposure limit.

Chemical name	<b>CAS</b> number	%	Number	Classification
(2-methoxymethylethoxy)propanol propane-1,2-diol		2.5 - 10 0.1 - 1		Not classified. [2] Not classified. [2]

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

### 4. FIRST AID MEASURES

### First-aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give

anything by mouth to an unconscious person. If unconscious, place in recovery

position and seek medical advice.

**Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do not use solvents or thinners.

**Eye contact**: Check for and remove any contact lenses. Immediately flush eyes with running water

for at least 15 minutes, keeping eyelids open.

**Ingestion**: If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do not induce vomiting.

Page: 1/5

### FIRE-FIGHTING MEASURES

**Extinguishing media** 

: Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders.

Extinguishing media not to

be used

: Do not use water jet.

Special exposure hazards

: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

### **ACCIDENTAL RELEASE MEASURES**

Personal precautions

: Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

**Environmental precautions** 

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Methods for cleaning up

: Preferably clean with a detergent. Avoid using solvents.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

### HANDLING AND STORAGE

**Handling** 

: Keep container tightly closed.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Put on appropriate personal protective equipment (see section 8).

Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

**Storage** 

: Store in accordance with local regulations. Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. Keep away from: oxidising agents, strong alkalis, strong acids.

No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Ingredient name **Occupational exposure limits** 

(2-methoxymethylethoxy)propanol EH40/2005 WELs (United Kingdom (UK), 8/2007). Absorbed

through skin.

TWA: 308 mg/m<sup>3</sup> 8 hour(s). TWA: 50 ppm 8 hour(s).

EH40/2005 WELs (United Kingdom (UK), 8/2007). propane-1,2-diol

TWA: 10 mg/m3 8 hour(s). Form: Particulate

TWA: 150 ppm 8 hour(s). Form: Sum of vapour and particulates TWA: 474 mg/m³ 8 hour(s). Form: Sum of vapour and particulates

Date of issue/Date of revision: 2010-01-22. Page: 2/5



### **EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Exposure controls**

: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

### Occupational exposure controls

Respiratory system

: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Skin and body

: Personnel should wear antistatic clothing made of natural fibres or of hightemperature-resistant synthetic fibres.

**Hands** 

: For prolonged or repeated handling, use the following type of gloves: **Gloves** 

Recommended: nitrile rubber

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Eyes Environmental exposure**  : Use safety eyewear designed to protect against splash of liquids.

controls

Do not allow to enter drains or watercourses.

#### PHYSICAL AND CHEMICAL PROPERTIES 9.

**Physical state** : Liquid.

Flash point : Not applicable.

**Density** : 1 g/cm<sup>3</sup>

Vapour density : < 1 (Air = 1) (Calculated value for the mixture)

**Explosion limits** : Greatest known range: Lower: 0.6% Upper: 20.4% (1-(2-butoxy-1-

methylethoxy)propan-2-ol)

### 10. STABILITY AND REACTIVITY

Conditions to avoid

: Stable under recommended storage and handling conditions (see section 7). When exposed to high temperatures may produce hazardous decomposition products.

**Materials to avoid** 

Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

**Hazardous decomposition** products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 11. TOXICOLOGICAL INFORMATION

There is no data available on the preparation itself. The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Date of issue/Date of revision : 2010-01-22. Page: 3/5

### 12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself.

Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

### **Aquatic ecotoxicity**

Conclusion/Summary : Not available.

Persistence/degradability

Conclusion/Summary : Not available.

PBT : Not applicable.

vPvB : Not applicable.

### 13. DISPOSAL CONSIDERATIONS

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

**Hazardous waste**: Within the present knowledge of the supplier, this product is not regarded as

hazardous waste, as defined by EU Directive 91/689/EEC.

### 14. TRANSPORT INFORMATION

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

### Land - road/railway

UN number : Not regulated.

Transport document name : Not applicable.

ADR/RID Class : Not applicable.

<u>Sea</u>

UN number : Not regulated.

Proper shipping name : Not applicable.

IMDG Class : Not applicable.

Marine pollutant : No.

Air

UN number : Not regulated.

Proper shipping name : Not applicable.

ICAO/IATA Classification : Not applicable.

This product is not regulated for carriage according to ADR/RID, IMDG, ICAO/IATA.

### 15. REGULATORY INFORMATION

<u>EU regulations</u>: The product is determined as not being dangerous according to the requirements of

the DPD.

Risk phrases : This product is not classified according to EU legislation.

Other EU regulations

Additional warning : Safety data sheet available for professional user on request.

phrases

The information in this Safety Data Sheet is required pursuant to Annex II to Regulation (EC) No 1907/2006.

Industrial use : The information contained in this safety data sheet does not constitute the user's

own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply

to the use of this product at work.

Date of issue/Date of revision : 2010-01-22. Page: 4/5



UC-PG

### **Unocryl Parkettgrund**

### **16. OTHER INFORMATION**

Date of issue/ Date of

: 2010-01-22.

revision

### **Notice to reader**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Page: 5/5 Date of issue/Date of revision : 2010-01-22.

