

Verzögerer VZ

Product description

Zweihorn Verzögerer is a solvent mixture used to retard the drying process.

Range of application

Zweihorn Verzögerer VZ is used to prevent formation of bubbles, flow problems (surface stress failures) or greying of the painted surface.

Zweihorn Verzögerer VZ can be universally used in all solvent-based Zweihorn varnishes, paints and stains.

Application

Recommended amount to be added (as required): 1 - 5%.

Product data

Batch size	1 l
Shelf life in unopened original batches	approx. 2 years

Further information can be obtained from the label and the Safety Data Sheet 91/155/EWG, which you can download from the Internet under www.zweihorn.com or which you can request from us.

Zweihorn products are produced for the professional user, who has a basic knowledge of the use and the application of stains, varnishes, glazes and glues. The user information for our qualities given in the leaflets should be regarded as non-binding recommendations. They are based on our test series and experiences and should facilitate and promote the work of our clients. Any adjustment to the individual working conditions, which might be possible, lies within your responsibility. If in any doubt, our material experts as well as our application and laboratory technicians will try to help you as best as they can. We guarantee of course the impeccable quality of our products based on our General Sales and Delivery Conditions. The use of the final product lies entirely within the responsibility of the buyer. As long as we have not guaranteed in writing specific characteristics and suitability of the products for a contractually agreed purpose, any advice or information given regarding the application, even if the advice or information is given to the best of our knowledge, will be non-binding. Nor does it relieve the buyer, either from his own inspection, and if need be through a trial processing. Furthermore, we are only liable according to Chapter 1 of our General Conditions for advice either given or rejected, which does not refer to the characteristics and use of the delivered product.

Applicable is the current Technical Data Sheet, which can be downloaded under www.zweihorn.com. Previous technical data sheets are voided with the issue of a new version.

Date of issue: 3. August 2006